

# Removal Instructions for Spring Garden Lamp Shade

Please read the following instructions thoroughly prior to unpacking your Spring Garden Lamp shade. The shade is packed well, however, there is a deep slot for the metal brace and if the shade is not removed as directed, the brace may break from the shade. Please see the images below.

1. Remove the cardboard from the styrofoam.
2. Gently slide your fingers under the shade on each side. Note: the center styrofoam should remain intact at this point.
3. Slowly pull upwards to remove the shade from the outer formed foam. The foam insert should remain in the shade.
4. Lay the shade on a stable surface and place the opening toward you. With one hand on the top of the foam insert and the other under it, slide the foam insert toward you from the lamp without disturbing the metal brace.



# Assembly Instructions

## CAUTION:

Read instructions carefully and turn electricity off at main circuit breaker panel before beginning installation

## WARNING

All wires are connected. When unpacking box, be careful not to pull wires, a bad connection may result from damage to the wires. Do not connect electricity until lamp is fully assembled. Unpack and place all parts on a flat surface or floor.

1. Remove (2) set screw from pin of upper metal frame.
2. Insert pin of upper metal frame into the hole on top of lower metal frame and secure with (2) set screws.
3. Position the lamp on the wall at desired location and mark the place for the anchors to be installed.
4. Drill pilot holes on the marked spots and insert plastic anchors. (If fastening with wood screws to stud, skip this step)
5. Screw (2) wood screws to the plastic anchors or the spots that you marked on stud
6. Secure the shade to the bracket with two screw
7. Raise the lamp to wall , hang the lamp with the (2) wood screws.
8. Attach lower metal frame to the wall , then secure the lamp to the plastic anchor or the spot that you marked on stud with a wood screw.
9. Install B 60 Watt Maximum medium base Type " A" bulb ( not included) into the socket .
10. Plug the Cord into an outlet and turn on at switch, your new lamp is ready for use .

